



US006652170B1

(12) **United States Patent**
Arnold

(10) **Patent No.:** **US 6,652,170 B1**
(45) **Date of Patent:** **Nov. 25, 2003**

(54) **PORTABLE PRINTER AND DATA ENTRY
DEVICE ASSEMBLY**

(75) Inventor: **Gregory B. Arnold**, Centerville, OH
(US)

(73) Assignee: **Paxar Americas, Inc.**, Dayton, OH
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 364 days.

(21) Appl. No.: **09/665,813**

(22) Filed: **Sep. 20, 2000**

Related U.S. Application Data

(63) Continuation-in-part of application No. 09/384,675, filed on
Aug. 27, 1999.

(51) **Int. Cl.⁷** **B41J 3/36**

(52) **U.S. Cl.** **400/88; 400/693; 347/222**

(58) **Field of Search** 400/88, 691, 693;
347/222

(56) **References Cited**

U.S. PATENT DOCUMENTS

D245,200 S * 7/1977 Packard D18/11
4,727,245 A * 2/1988 Dobbins et al. 235/432 X
4,734,710 A * 3/1988 Sato et al. 235/432 X
4,788,658 A * 11/1988 Hanebuth 361/684
5,047,615 A * 9/1991 Fukumoto et al. 235/432
5,057,676 A * 10/1991 Komaki 235/432
5,237,487 A * 8/1993 Dittmer et al. 361/729
5,371,348 A * 12/1994 Kumar et al. 235/472.02
5,468,947 A * 11/1995 Danielson et al. 235/472.02
5,483,624 A 1/1996 Christopher et al. 395/117
5,486,259 A 1/1996 Goodwin et al. 156/384
5,488,558 A * 1/1996 Ohki 701/207
5,808,283 A * 9/1998 Stanton et al. 235/432 X
5,816,725 A * 10/1998 Sherman et al. 235/472.01 X
5,930,770 A * 7/1999 Edgar 235/462.43 X
6,010,067 A * 1/2000 Elbaum 235/380
6,195,589 B1 * 2/2001 Ketcham 700/28

FOREIGN PATENT DOCUMENTS

EP 0 191 495 8/1986
EP 0 199 252 10/1986
EP 0 200 945 11/1986
EP 0 250 910 1/1988
JP 5-108522 * 4/1993
JP 11138911 A * 5/1999 B41J/3/36
JP 2000025304 A * 1/2000 B41J/29/38

OTHER PUBLICATIONS

Symbol Technologies, Inc. manual entitled SPT 1500, pp. 1
through 20, Copyright 1998.

Symbol Technologies, Inc. internet site, Product Information,
SPT 1500 Palm Terminal Series, pp. 1 through 3, Mar.
23, 1999.

Axiom Thermal Printer Mechanism, User's Manual THTP
Series, Preliminary Issue, reference 3104660-FDE, Oct.
1998.

Symbol Technologies, Inc., internet site, MSR 3000 Mag-
netic Stripe Reader For SPT 1700 and PPT 2700 Pocketable
Computers, pp. 1 through 3, Feb. 3, 2000.

Symbol Technologies, Inc., internet site, PPT 2700 Series
Palm-size PC's, pp. 1 through 3, Feb. 3, 2000.

Fujitsu FTP 638 MCL100 (print head), two pages.

Publication, Semtek, Model 908X, 608X, 408X (card
reader), one page.

Solvepoint DockV™ and DockV Pro™ Instruction Guide,
copyright 1999-2000, two pages.

PalmV(x)™ adapter for PalmIII accessories, one page.

* cited by examiner


Primary Examiner—Daniel J. Colilla

(74) *Attorney, Agent, or Firm*—Joseph J. Grass

(57) **ABSTRACT**

There is disclosed an assembly of a portable data entry
device and a portable printer. The printer is hand-held and
carries the data entry device. The data entry device includes
a scanner and is located at the front portion of the printer.
The printer has a space for accommodating a label roll and
a print module which are located at the rear portion of the
printer. The printer can be used with different data entry
devices by use of adapters.

14 Claims, 5 Drawing Sheets








FIG-4




FIG-5




FIG-6





FIG-7









FIG-12




FIG-14




FIG-15




FIG-13





FIG-16



1

PORTABLE PRINTER AND DATA ENTRY DEVICE ASSEMBLY

CROSS-REFERENCE TO RELATED APPLICATION

This is a continuation-in-part of co-pending application Ser. No. 09/384,675, filed Aug. 27, 1999.

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to the fields of portable printers and portable data entry devices.

2. Brief Description of the Prior Art

The following prior art is made of record: U.S. Pat. Nos. 5,486,259 and 5,483,624; Symbol Technologies, Inc. manual entitled SPT 1500, pages 1 through 20, Copyright 1998; Symbol Technologies, Inc. internet site, Product Information, SPT 1500 Palm Terminal Series, pages 1 through 3, Mar. 23, 1999; Axiohm Thermal Printer Mechanism, User's Manual THTP Series, Preliminary Issue, reference 3104660-FDE, October, 1998.

SUMMARY OF THE INVENTION

The invention relates to a portable printer which can be coupled to a portable data entry device, and when so coupled the combination is a portable assembly which in general can be conveniently carried from place-to-place and which in particular is hand held.

The invention relates to an improved lightweight, portable, hand-held, user-friendly printer for reception of a lightweight, portable hand-held, user-friendly data entry device, and to a combination of such a printer and such a data entry device.

It is a feature of the invention to provide an improved printer adapted to receive portable data entry devices having different shapes. In particular, different models of portable data entry devices of the same or different manufacturers are shaped differently. In order to have various portable data entry device piggyback onto the printer without redesigning the printer, an adapter or adjuster is provided to accommodate differently shaped data entry devices.

According to a specific embodiment of the invention, a set of adapters is provided to receive correspondingly shaped portable data entry devices. Instead of redesigning the printer housing for each different data entry device, a different adapter is provided and each adapter is shaped to fit with a corresponding data entry device. Depending on the shape of the data entry device to be used, the adapter corresponding to that data entry device is assembled along with the remainder of the housing when the printer is being manufactured. Alternatively, in the event a printer has an adapter for one data entry device, the printer can be readily made to accommodate another and differently shaped data entry device by matching a different adapter to that other data entry device and substituting it on the printer housing.

It is another feature of the invention to provide an improved portable printer having a lower housing section, an upper housing section, and a compartment connected to the upper housing section for receiving a portable data entry device in piggyback fashion. One or more printed circuit boards are disposed between the upper and lower sections. There is a battery compartment in the lower housing section, and a card reader and a printer module including a print head are mounted on the circuit board. The card reader is disposed

2

between the compartment and the printhead. An improved elastomeric grip includes an actuator and a data port plug. A specific embodiment of the printer includes an elongate hand-held housing having a front portion which has a compartment or pocket for receiving a data entry device. The housing also has a rear portion. There is space at the rear portion for receiving a roll of a label web. A print module or mechanism is disposed at the rear portion for printing on the label web, and the print module including a thermal print head and a platen roll cooperable with the print head. It is preferred that the housing compartment have an open top for access to the data entry device. The platen roll is preferably mounted on a cover for an access opening to the label roll space. A set of batteries and the print module are preferably mounted on an elongate circuit board disposed in the printer housing. The batteries are preferably located at the front portion of the printer housing. The compartment is preferably open-fronted and is channel-shaped for slidably, receiving the data entry device.

BRIEF DESCRIPTION OF THE DIAGRAMMATIC DRAWINGS

FIG. 1 is a perspective view of an assembly of a portable printer and portable data entry device, which is hand-held and portable, showing the portable data entry device scanning a bar-coded label;

FIG. 2 is a partly exploded perspective view of the portable printer and the portable data entry device separated and with the cover open;

FIG. 3 is a generally vertical sectional view of the assembly shown in FIG. 1;

FIG. 4 is a perspective view of a printed circuit board of the printer with batteries and a print module shown mounted thereon;

FIG. 5 is an elevational view of one of the two mirror-image housing sections;

FIG. 6 is a fragmentary sectional view illustrating the channel shape of the compartment for receiving the portable data entry device;

FIG. 7 is a fragmentary perspective view of the print module and the cover and the platen roll mounted by the cover;

FIG. 8 is a partially exploded perspective view of a portable printer including a compartment or adapter for receiving a portable data entry device;

FIG. 9 is an exploded perspective view of a different adapter for use with a different data entry device;

FIG. 10 is a perspective view similar to FIG. 9 but showing yet another different adapter for use with yet another different data entry device;

FIG. 11 is a bottom plan view, partly in section, of the adapter shown in FIG. 8;

FIG. 12 is a perspective view of the printer shown in FIG. 8 removably coupled to the portable data entry device;

FIG. 13 is an exploded perspective view of the printer shown in FIGS. 8 and 12;

FIG. 14 is a perspective view showing the underside of the adapter also shown in FIGS. 8 and 11, together with a connector;

FIG. 15 is a generally vertical sectional view of the printer and data entry device of the embodiment of FIGS. 8 and 11 through 14; and

FIG. 16 is a sectional view taken at line 16—16 of FIG. 13.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

With reference to FIG. 1, there is shown an assembly generally indicated at 10 of a portable printer generally indicated at 11 and a portable data entry device generally indicated at 12. The printer 11 and the device 12, individually, as well as the assembly 10 are portable and in particular are hand-held for ease of use. The device 12 includes a scanner 13 at its front end for scanning a bar-coded label L. The device 12 also has manually operable keys 14 and a display 15. The scanner 13, the keys 14 and the display 15 are housed in an elongate relatively thin housing 16. Manually depressing buttons 14' operates the scanner 13.

The printer 11 is shown to have an elongate housing 17 having opposed mirror-image housing sections 18 and 19. The front portion of the housing 17 has a compartment or space or pocket 20 for receiving and releasably holding the data entry device 12. The compartment 20 has an open top 21 to enable the keys to be operated and to enable the display 15 to be seen. The compartment 20 is channel-shaped as diagrammatically depicted in FIG. 6 to capture the data entry device 12. As shown, the housing 17 has flanges 22 and 23 which help retain the device 12 captive in the compartment 20. The front end of the compartment 20 is open as indicated at 24 to enable the device 12 to be slid into the compartment 20. The device 12 is releasably latched in the compartment 20 by opposed latches 25. The latches 25 are each comprised of a pad 26 flexibly secured to a wall 27. The pads 26 have opposed projections 28 which are received in recesses 29 in the housing 16 of the device 12. By simultaneously depressing both pads 26 rearwardly of the wall 27, the projections 28 are withdrawn from the recesses 29 which allows the device 12 to be slid out of the compartment 20.

The underside of the device 12 has a 10-pin connector 30 which cooperates with a mating 10-pin connector 31 on the housing 17. As the device 12 is slid into the compartment 20 in the direction of arrow A in FIG. 2, the connector 30 at the rear end of the device 12 connects with the connector 31 at the rear end of the compartment 20, thereby enabling the data entry device 12 to control the printer 11. The latches 25 are latched when the connectors 30 and 31 are connected.

As is apparent from FIG. 3, the underside of the printer housing 17 has a hollow or concave surface 32 for receiving the palm of the user's hand. A strap 33 can fit about the back of the user's hand. The strap 33 can be a continuous loop of a band as shown in FIG. 3. FIG. 3 also shows the device 12 diagrammatically and that a label roll R and a prior art print module or print mechanism generally indicated at 34 are disposed at a rear portion of the printer 11. The label roll R is illustrated as being comprised of a label web (or a web of labels) W received in space 35 in the housing 17. The roll R is suitably supported either at its central opening 36 or simply in a cradle 37 as shown. The web W passes from the roll R between a thermal print head 38 and a platen roll 39. The printed label web W exits the housing 17 at a slot 40 one side of which is formed by a tear edge 41.

FIG. 7 shows that the print module 34 comprises a frame 42 which has sockets 43 and 44. The module 34 includes a platen roll 39 having a shaft 46. The shaft 46 is releasably held in the sockets 43 and 44 in the FIG. 3 position. The module 34 further includes an electric motor 47 and gearing generally indicated at 48. The gearing 48 includes gear 49 on the shaft 46. Springs 50 which bear against a support 51 resiliently mount the print head 38.

The platen roll 45 is rotatably mounted to a cover 52. In particular, the shaft 46 passes through a flange 53 and is

removably received in a C-shaped cutout 54 in a flange 55. The end of the cover 52 opposite the platen 45 has a pair of outwardly extending projections 56 for receipt in opposed recesses 57 in the housing sections 18 and 19. Accordingly, the cover 52 is pivotally mounted for movement between a closed or operating position shown in FIGS. 1 and 3 and an open or non-operating position as illustrated in FIG. 2. It is apparent when the cover 52 is in the position shown in FIG. 2, a label roll R can be readily inserted into the space 35. If the roll R has a core C as shown the core can be readily removed. Also, the print head 38 and the platen roll 39 can be readily cleaned when the cover is in the open position. If required, the platen roll 45, its shaft 46 and its gear 49 can be readily replaced by snapping the portion of the shaft 46 between the flanges 55 and the gear 49 out of the socket 44, and pulling the other end of the shaft 46 out of the hole in the flange 53.

As best shown in FIG. 4, the print module 34 and upstanding battery contacts 58 are mounted on a printed circuit board 59. The connector 31 is connected to the printed circuit board 59 via conductors 31'. A ribbon connector 60 connects the print head module 34, particularly the motor 47, the print head 38 and sensors (not shown) to the printed circuit board via a connector 61. There are four contacts 58 on each side of the printed circuit board 59 for releasable contact to four rechargeable batteries 62. The connector 31 which is mounted to a support 63 is connected to the printed circuit board 59. A port 64 accessible from outside the housing 17 is connected to the printed circuit board 59. The batteries 62 are held in a holder generally indicated at 64 which holds the batteries 62 in position but keep the batteries 62 from touching each other. The holder 64 maintains the batteries 62 aligned with opposed pairs of contacts 58. The holder 64 surrounds the outsides of all the batteries 62 as best shown in FIG. 4. The holder 64 has fin-like separators 65 joined to a peripheral wall 66 and to a bottom wall 67 (FIG. 3). The bottom wall 67 is connected to the printed circuit board 59 by integrally molded pins 68. The holder 64 is particularly beneficial in the event the assembly 10 or the printer 11 is dropped or otherwise impacted.

The printed circuit board 59 is captive between the housing sections 18 and 19 in transverse slots 69 and 70. The support 63 is received in slots 71 and 72. The housing sections 18 and 19 are connected by screws (not shown) received in aligned holes 74.

Floor 75 of the compartment 20 is provided with an access opening 76 which is closed off by a cover 77. The door 77 is pivotally mounted about a hinge axis 78 for movement between the closed position shown in FIG. 2 and an open position to provide access for loading and removing the batteries 24. The cover 77 is releasably held in the closed position by a releasable latch 78'.

The printer 11 is compact, by way of example not limitation, one embodiment of the printer 11 has a length of about 8.31 inches (211 mm), a height 2.38 inches (60 mm), a width of 3.38 inches (86 mm) and a weight of 0.9 pound (0.4 kg.); and the data entry device 12 has a length of 5.46 inches (140 mm), a height of 0.66 inch (17 mm), a width of 3.16 inches (81 mm), and a weight of 6.1 ounces (0.17 kg).

With reference to FIG. 8, there is shown the portable data entry device 12 and a printer 80. The printer 80 has an elongate housing 81 having a lower housing section 82 and an upper housing portion 83. An adapter or adjuster 84 is connected to the upper housing section 83 by a plurality of threaded fasteners 85. The adapter 84 together with upper

surface **86** of the housing section **82** forms a compartment **87** for receiving the data entry device **12** in piggyback fashion as shown in FIGS. **12** and **15**.

FIGS. **8**, **9** and **10** show a set of three different adapters **84**, **84'** and **84''** and a set of three corresponding different data entry devices **12**, **12'** and **12''**. Thus, the adapter **84** is shaped to fit or accommodate the data entry device **12**, the adapter **84'** is shaped to fit or accommodate the data entry device **12'**, and the adapter **84''** is shaped to fit or accommodate the data entry device **12''**. As shown the data entry device **12'** is narrower than the data entry device **12** and the data entry device **12''** is thicker than the data entry devices **12** and **12'**. It is thus apparent that the printer **81** can be readily modified or adjusted to accommodate different data entry devices.

The adapters **84**, **84'** and **84''** are all shown to have a generally U-shaped configuration and are each preferably of one-piece molded construction. The adapter **84** has vertically extending wall sections **88** and **89** and a wall section **90**. The wall sections **89** and **90** are parallel and the wall sections **88** are generally parallel to each other. Opposed faces of the wall sections **88** have frictional or gripper members **91** which grip the housing **16** of the data entry device **12**. The housing **16** of the device **12** also has a lip or gripper **16'** which cooperates with a ridge **93'** on the adapter **84** to help releasably hold the device **12** to the printer **80**. Alternatively, or in addition, it is preferred that the adapter **84** be comprised of an elastomeric material which will enable the data entry device to be yieldably held in the docked position in the compartment **87**. Thus, the data entry device **12** is frictionally held in the compartment **87** by the gripper members **91** and **93'**. The wall sections **88** and **90** are integrally joined to a horizontally extending U-shaped retaining flange **92**. The compartment **87** is provided by the wall sections **88** and **90**, the flange **92** and the upper surface **86** of the upper housing section **83**. End edge portion **93** is sculptured or tailored to the data entry device **12** so that keys **14** can be operated while the data entry device **84** is docked in the compartment **87**. The top portion of the adapter **84** is open, in the same way as the compartment **20** is open to enable the display **15** to be seen.

The data entry device **12'** is narrower than the data entry device **12** and thus the distance between walls **88'** is less than the distance between the walls **88** so as to fit or accommodate the data entry device **12'** between wall sections **88'**.

The data entry device **12''** has a different arrangement of buttons **14''** than the data entry devices **12** and **12'** and as such the horizontal flange **9''** is sculptured or tailored to allow access to the buttons **14''**.

In other respects the adapters **84'** and **84''** are identical to the adapter **84**. As seen in FIGS. **8**, **13** and **14**, a coupling **C** in the form of a connector generally **94** is secured by screws **95** to the top or flange **92**. The wall section **90** has a stepped opening **96** (FIG. **14**). The connector **94** has a vertical collar **97** and a horizontal bar **98**. The wall **90** is positioned between the collar **97** and the bar **98** to help hold the connector **94** in position on the adapter **84**. The connector **94** is also positioned against an upstanding projection **99** on the upper housing section **83**. The front upper portion of the connector **94** has a plurality of contacts **100** for contacting mating contacts on the data entry device **12**.

As seen in FIG. **12** for example, the printer **80** and the data entry device **12** are used in the same manner as in the embodiment of FIGS. **1** through **7**. The data entry device **12** is disposed at a front portion of the printer housing **81**. A printer module **101** and space **S** defined by a surface **81'** for mounting a label supply roll **R** are disposed at the rear

portion of the housing **81** and a magnetic card reader generally **102** is disposed between the data entry device receiving compartment **87** and the print head module **101** with its print head **101'**. So, therefore, data can be printed by the printer **80** from data received from the data entry device **12**, from the card reader **102** or through data ports **103** or **104** (FIG. **13**).

The data ports **103** and **104** are mounted on a U-shaped printed circuit board **105**. The printed circuit board **105** is electrically connected to a printed circuit board **106**. Conductor **107** is shown to connect the connector **94** to the printed circuit board **106**. The print head module **101** and the card reader **102** are mounted on and are electrically connected to the printed circuit board **106**.

As shown in FIG. **13**, the housing section **81** has a pair of longitudinally extending horizontal lands **108** which support side margins of the printed circuit board **106**. The lands **108** are joined to a pair of parallel, vertical, opposed walls **109**. The printed circuit board **105** is secured to a rigid post **110** by a screw **111** between the walls **109**. The lands **108** have holes **112** through which screws **85** pass into the adapter **84**. In this way the adapter **84** is held securely to the lower housing section **82** and to the upper housing section **83**.

The upper housing section has an inclined portion **113** with a door **114** pivotally mounted on spaced arms **113'** by two studs **115** received in opposed holes **116**. The door **114** rotatably mounts a platen roller **117** which cooperates with the print head **101'** as shown in FIG. **15**. The door **114** has a flexible handle **118** for assisting the user in opening the door **114**.

The card reader **101** is used to read a magnetic card MC. The adapter **84** and the adjacent wall **113''** of the inclined portion **113** are spaced to provide a slot **S'** so that the magnetic card MC can pass therethrough between members **119** and **120**. The card reader **102** has a pair of U-shaped members **119** and **120**. The member **119** is positioned at opening **121** in the adapter **84**. The other member **120** is positioned at an opening **121'** of the inclined portion **113** (FIG. **15**). When the print head module **101** prints, the printed labels **L** issue through an opening **122** in the inclined portion **113**.

As best shown in FIG. **13**, a pair of manually engageable members **123** and **124** are secured to the outside surfaces of walls **109**. The members **123** and **124** are identical except that the member **123** has a differently shaped rectangular plug **125** from rectangular plug **126** of the member **124**. The plug **125** fits into a hole **127** and the plug **126** fits into a hole **127'**. The members **123** and **124** are each of one-piece molded, resilient, elastomeric construction. Each member **123** and **124** has inner surfaces with three identical undercut projections **128**. The projections **128** fit through holes **129** in the walls **109** and are captured at the undercut **130** as best shown in FIG. **16**. The inside surfaces of the members **123** and **124** from which the projections **128** extend also have a raised or convex portion **131**. Each convex portion **131** is aligned with a switch **132**. If either switch **132** is depressed the scanner **13** will be operated to read the bar code on the label **L**. Convex portions **133** on the outside surfaces of each of the members **123** and **124** are aligned with the convex portions **131** and are depressible by the user to operate the switches **132**. The plugs **125** and **126** are preferably positioned in respective openings **127** and **127'** when the ports **103** and **104** are not in use. However, by flexing the members **123** and/or **124** to their phantom line positions shown at PL in FIG. **13**, the respective ports **103** and **104** can be uncovered for use.

The lower housing section has a compartment **134** for receiving a battery **135** connected to the printed circuit board for powering the printer and its electronics. A door **136** closes the compartment **134**.

By way of example, not limitation, the print head module **101** can be a Fujitsu FTP 638MCL100 print head module and the card reader **102** can be a Semek 4083-0 card reader.

Other embodiments and modifications of the invention will suggest themselves to those skilled in the art, and all such of these as come within the spirit of this invention are included within its scope as best defined by the appended claims.

What is claimed is:

1. In combination: a portable printer, at least two differently shaped portable entry devices, each portable entry device including a scanner for scanning bar codes and a data entry device housing for the scanner, the portable printer including a printer housing having a front portion, a set of at least two different adapters each shaped to receive one of the data entry devices, one of the adapters being disposed at the front portion, the printer housing having a rear portion, the printer housing providing space at the rear portion for receiving a roll of a label web, a print head disposed at the rear portion of the printer housing, and a data coupling between the received data entry device and the printer.

2. In combination: a portable printer, at least two differently shaped portable data entry devices, the printer including a printer housing, a print head disposed in the housing, at least two different adapters each shaped to receive one of the data entry devices, the printer housing including one of the adapters, and a data coupling between the received data entry device and the printer.

3. In the combination defined in claim 2, including a compartment on the housing for a battery to power the print head.

4. A portable printer, comprising: a housing, a print head in the housing, a set of at least two different shaped adapters, the housing including one of the adapters, and each adapter being shaped to receive a correspondingly shaped portable data entry device.

5. A portable printer as defined in claim 4, wherein each adapter is generally U-shaped.

6. A portable printer as defined in claim 4, and a fastener for connecting one of the adapters to the remainder of the housing.

7. A portable printer as defined in claim 4, wherein each adapter has an open top portion to allow operation of the portable data entry device.

8. A portable printer as defined in claim 4, wherein each adapter has an open front portion.

9. A portable printer as defined in claim 4, including a battery for powering the print head.

10. A portable printers defined in claim 4, wherein each adapter has an open front portion and an open top portion.

11. A portable printer as defined in claim 4, including a data connector secured to the adapter on the housing.

12. A portable printer as defined in claim 4, including a frictional member for releasably holding a data entry in the adapter on the housing.

13. A portable printer as defined in claim 4, wherein each adapter includes a flange for helping to removably retain a data entry device on the housing.

14. A portable printer as defined in claim 4, wherein each flange is generally U-shaped.

* * * * *